

## General Description:

The FHP series of Power Meter are designed for use with an Optical Source for performing optical loss measurements on fiber optic cables.



## Specifications:

	FHP1A02	FHP1B02
Wavelength (nm)	850/1300/1310 /1490/1550/1625	
Connector	InGaAs	
Detector Type	FC/PC SC/PC ST/PC Universal	
Accuracy <sup>①</sup>	± 0.35dB±10nW	
Resolution	0.01dB	
Linearity	±5%	
Auto Power Off	Yes	
Back Light	Yes	
Reference Value	Yes	
Measuring Range(dBm)	-60 to +3	-40 to +23
USB Interface	N/A	
Data Storage	N/A	
Wavelength Recognize	N/A	
Tone Detection (Hz)	N/A	
Operating Temperature	-10 to +50℃	
Storage Temperature	-20 to +70℃	
Power Supply	2pcs*Li-ion Battery; 5V AC/DC Adaptor	
Dimension (mm)	115L*62W*30H	
Net Weight	140g	

Note: <sup>①</sup> Valid at 1550nm, CW, 23±3℃, Relative Humidity ≤70%, with an FC connector.

## Ordering Information:

### Standard Accessories:

FC/PC,SC/PC,ST/PC interchangeable connector, Manual, Carrying Bag, AC/DC adapter, Test Report.